


AGM-101A0-I1-R

**Based on T5L ASIC 10.1 Inches, 1024xRGBx600, 16.7M Colors, IPS screen
RTP, Standard instruction set (TA) / DGUS II system, Cost-Effective
screen**



Record of Revision

Revise Date	Content
2019-03-22	First Edition
2019-08-22	Modify Interface

● Display

Item	Parameter	Description
Color	16.7M (16777216) colors	24 bit color 8R8G8B
(A.A)	222.7 mm (W) × 125.3 mm (H)	1024x600
(V.A)	225.7 mm (W) × 127.6 mm (H)	1024x600
Resolution	1024x600	Support 0° /90° /180° /270° rotated display
Backlight	LED	≥ 10000H (Continuous working with maximum brightness, time of brightness halves)
Brightness	200nit	TA system: 64 levels adjustment; DGUS II system:100 levels adjustment (It's not recommend to set brightness to 1%~30% of the maximum which may lead a flicker)

Note: Displaying of high-contrast still images for more than 30 minutes may result in residual images. Please add screen saver to avoid this problem.

● Voltage & Current

Item	Conditions	Min	Typ	Max	Unit
Power Voltage	-	6.0	12.0	15.0	V
Operation Current	VCC = +12V, Backlight on	-	250	-	mA
	VCC = +12V, Backlight off	-	70	-	mA

Recommended power supply: 12V 1A DC

● Reliability Test

Item	Conditions	Min	Typ	Max	Unit
Working Temperature	60%RH at 12V voltage	-20	25	70	℃
Storage Temperature	-	-30	25	85	℃
Working Humidity	25℃	10%	60%	90%	RH
Protective Paint	-	-	None	-	-

● Interface

Item	Conditions	Min	Typ	Max	Unit
Baudrate	User Set	3150	115200	3225600	bps
Output Voltage (TXD)	Output 1, Iout = -4mA	2.7	3.2	-	V
	Output 0, Iout = 4mA	-	0.1	0.4	V
Input Voltage (RXD)	Input 1	2.4	3.3	5.5	V
	Input 0	0	-	1.0	V
Interface	Mode is determined by Jumper: ON = 8N1, 3.3V & 5V TTL/CMOS; OFF = 8N1, RS232				
Socket	8Pin_2.0mm Lock Socket				
USB	None				
SD Slot	YES (SDHC/FAT32 Format)				

- **Memory**

Item	Typical value	Features	Typ value	Unit	Description
FLASH (TA/DGUS II)	16Mbytes	Space of Font	4-12	Mbytes	A single font of 256Kbytes, store font, icon libraries, and other binary files
		Picture Storage (.ICL file)	12-4	Mbytes	JPEG format (Picture quantity relate to JPEG size, size of a single JPEG image file should not exceed 768 Kbytes)
RAM (DGUS II)	128Kbytes	Variable Storage Space	/	/	Data is not saved when power down
Nor Flash (DGUS II)	320Kbytes	User database	/	/	Data is saved when power down

- **UI & Peripheral**

UI & Peripheral	
UI Version	TA / DGUS II (DGUS II pre-installed)
Peripheral	Resistive touch screen, Buzzer

- **Packing Capacity & Dimension**

Dimension				
Dimension	257.8(W) × 148.1(H) × 15.1(T) mm			
Net Weight	530g			
Packing Capacity				
Model	Size	Layer	Quantity/Layer	Quantity(Pcs)
1 Carton1:	220mm(L)×160mm(W)×47mm (H)	-	-	-
2 Carton2:	250mm(L)×200mm(W)×80mm (H)	2	1	2
3 Carton3:	320mm(L)×270mm(W)×80mm (H)	-	-	-
4 Carton4:	450mm(L)×350mm(W)×300mm(H)	1	10	10
5 Carton5:	600mm(L)×450mm(W)×300mm(H)	-	-	-

Remark: there is no extra-notice if the product design changes that do not affect performance parameters and use.

